

FUENTES DE VOLTAJE SWITCHHEADAS (HP HIGH PERFORMANCE)

FUENTES DE MONTAJE EN SUPERFICIE (GARANTÍA 3 ÑOS)

UNA SALIDA

MODELO	VOLTAJE SALIDA	V. ENTRADA	DIMENSIONES	MODELO	VOLTAJE SALIDA	V. ENTRADA	DIMENSIONES		
TPS-15-5HP	5V/3A/15W	85-264VCA/ 120-370VCD	62.5X51X28MM	TPS-150-5HP	5V/26A/130W	88-132VCA, 176-264VCA Select. Por switch 248-373VCD	199X98X38MM		
TPS-15-12HP	12V/1.3A/15W			TPS-150-12HP	12V/12.5A/150W				
TPS-15-24HP	24V/0.625A/15W			TPS-150-24HP	24V/6.5A/156W				
TPS-15-48HP	48V/0.31A/15W			TPS-150-48HP	48V/3.3A/158W				
TPS-25-5HP	5V/5A/25W	88-264VCA/ 125-373VCD	78X51X28MM	TPS-180-12	12V/15A/180W	85-265VCA	199X110X50MM		
TPS-25-12HP	12V/2.1A/25W			TPS-200-5HP	5V/40A/200W	90-132VCA/ 180-264VCA por switch 254-370VCD	215X115X50MM		
TPS-25-24HP	24V/1.1A/26W			TPS-200-12HP	12V/17A/204W				
TPS-25-48HP	48V/0.57A/27W			TPS-200-24HP	24V/8.8A/211W				
TPS-35-5HP	5V/7A/35W			85-132VCA/ 176-264VCA	99X82X36MM	TPS-200-48HP	48V/4.4A/211W	90-132VCA/ 180-264VCA	215X115X50MM
TPS-35-12HP	12/3A/36W					TPS-240-12*	12V/20A/250W		
TPS-35-24HP	24V/1.5A/36W					TPS-240-24*	24V/10A/250W		
TPS-35-48HP	48V/0.8A/38W	TPS-350-12*	12V/30A/350W						
TPS-35-12	12V/3A/36W	TPS-350-5HP	5V/60A/300W						
TPS-35-24	24V/1.5A/36W	85-132VCA/ 176-264VCA	93X78X67MM	TPS-350-12HP	12V/29A/348W	85-132VCA/ 176-264VCA	190X93X65MM		
TPS-50-5HP	5V/10A/50W	88-132VCA/ 125-373VCD	99X97X36MM	TPS-350-24HP	24V/14.6A/350W	90-132VCA/ 180-264VCA	215X115X50MM		
TPS-50-12HP	12V/4.2A/50W			TPS-350-48HP	48V/7.3A/350W	90-132VCA/ 180-264VCA por switch 254-370VCD	225X124X50MM		
TPS-50-24HP	24V/2.2A/53W			TPS-450-5HP	5V/75A/375W				
TPS-50-48HP	48V/1.1A/53W			TPS-450-12HP	12V/37.5A/450W				
TPS-60-12	12V/5A/60W	85-132VCA/ 176-264VCA	159X98X38MM	TPS-450-24HP	24V/18.8A/451W	90-132VCA/ 180-264VCA por switch 254-370VCD	247X127X63.5MM		
TPS-60-24	24V/2.5A/60W			TPS-450-48HP	48V/9.4A/451W				
TPS-75-5HP	5V/12A/60W	88-264VCA/ 125-373VCD	129X97X38MM	TPS-600-5HP	5V/100A/500W	90-132VCA/ 180-264VCA por switch 254-370VCD	278X127X63.5MM		
TPS-75-12HP	12V/6A/72W			TPS-600-12HP	12V/50A/600W				
TPS-75-24HP	24V/3.2A/77W			TPS-600-24HP	24V/25A/600W				
TPS-75-48HP	48V/1.6A/77W			TPS-600-48HP	48V/12.5A/600W				
TPS-100-5HP	5V/16A/80W			85-132VCA/ 176-264VCA	159X97X38MM			TPS-1000-5HP	5V/150A/750W
TPS-100-12HP	12V/8.5A/102W	TPS-1000-12HP	12V/83.3A/1000W						
TPS-100-24HP	24V/4.5A/108W	TPS-1000-24HP	24V/41.7A/1000W						
TPS-100-48HP	48V/2.3A/110W	TPS-1000-48HP	48V/20.8A/1000W						
TPS-100-12	12V/8.5A/102W	85-132VCA/ 176-264VCA	199X98X38MM	TPS-1500-5HP	5V/300A/1500W	180-264VCA/ 254-37VCD	278X177.8X63.5MM		
TPS-100-24	24V/4.5A/108W			TPS-1500-12HP	12V/125A/1500W				
TPS-150-24	24V/6.5A/156W			TPS-1500-24HP	24V/62.5A/1500W				
				TPS-1500-48HP	48V/31.3A/1502W				



TPS-15



TPS-25



TPS-50



TPS-100



TPS-200



TPS-350



TPS-450



TPS-600



TPS-1000



TPS-1500

FUENTES DE VOLTAJE SWITCHEADAS (HP HIGH PERFORMANCE)

FUENTES DE MONTAJE EN SUPERFICIE (GARANTÍA 3 ÑOS)

DOS SALIDAS

MODELO	VOLTAJE SALIDA	V. ENTRADA	DIMENSIONES
TPRD-35AHP	5V/4A, 12V/1A, 32W	88-264VCA/ 125-373VCD	99X82X36MM
TPRD-35BHP	5V/2.2A, 24V/1A, 35W		
TPRD-50AHP	5V/6A, 12V/2A, 54W		99X97X36MM
TPRD-50BHP	5V/4A, 24V/1.4A, 53W		
TPRD-65AHP	5V/6A, 12V/3A, 66W		129X98X38MM
TPRD-65BHP	5V/4A, 24V/2A, 68W		
TPRD-85AHP	5V/8A, 12V/4A, 88W		159X97X38MM
TPRD-85BHP	5V/8A, 24V/2A, 88W		
TPRD-125AHP	5V/7.7A, 12V/7.7A, 130W	88-132VCA/ 176-264VCA Select. Switch 248-373VCD	199X98X38MM
TPRD-125BHP	5V/4.64A, 24V/4.6A, 133W		



TPRD-35/50/65/125



TRES SALIDAS

MODELO	VOLTAJE SALIDA	V. ENTRADA	DIMENSIONES
TPRT-50AHP	5V/4A, 12V/2A, -5V/0.5A, 46W	88-264VCD/ 125-373VCD	99X97X36MM
TPRT-50BHP	5V/4A, 12V/2A, -12V/0.5A, 50W		
TPRT-50CHP	5V/4A, 15V/1.5A, -15V/0.5A, 40W		
TPRT-50DHP	5V/3A, 24V/1A, 12V/1A, 51W	88-264VCA/ 125-373VCD	129X98X38MM
TPRT-65AHP	5V/6A, 12V/2.8A, -5V/0.5A, 66W		
TPRT-65BHP	5V/5A, 12V/2.8A, -12V/0.5A, 64W		
TPRT-65CHP	5V/5A, 15V/2.2A, -15V/0.5A, 65W		
TPRT-65DHP	5V/4A, 24V/1.5A, 12V/1A, 68W	88-264VCA/ 125-373VCD	159X97X38MM
TPRT-85AHP	5V/8A, 12V/3.5A, -5V/0.5A, 84W		
TPRT-85BHP	5V/8A, 12V/3.5A, -12V/0.5A, 88W		
TPRT-85CHP	5V/7A, 15V/3A, -15V/0.5A, 87W		
TPRT-85DHP	5V/6A, 24V/2A, 12V/1A, 90W	88-132VCA/ 176-264VCA Select. Switch 248-373VCD	199X98X38MM
TPRT-125AHP	5V/12A, 12V/5.5A, -5V/1A, 131W		
TPRT-125BHP	5V/12A, 12V/5A, -12V/1A, 132W		
TPRT-125CHP	5V/10A, 15V/4.5A, -15V/1A, 132W		
TPRT-125DHP	5V/8A, 24V/3A, 12V/2A, 136W		

CUATRO SALIDAS

MODELO	VOLTAJE SALIDA	V. ENTRADA	DIMENSIONES
TPQ-50BHP	5V/5A, 12/1A, -5V/0.5A, 45W	88-264VCA/ 125-373VCD	99X97X36MM
TPQ-50CHP	5V/5A, 15/1A, -5V/0.5A -15V/0.5A, 50W		
TPQ-50DHP	5V/3A, 12/1A, 24V/0.9A, -12V/0.5A, 53W		
TPQ-65BHP	5V/6A, 12/2A, -5V/0.5A, -12V/0.5A, 62W	88-264VCA/ 125-373VCD	129X98X38MM
TPQ-65CHP	5V/5A, 15/2A, -5V/0.5A, 15V/0.5A, 65W		
TPQ-65DHP	5V/4A, 12/1.5A, 24V/1A, -12V/0.5A, 68W	88-264VCA/ 125-373VCD	159X97X38MM
TPQ-85BHP	5V/7A, 12V/3.1A, -5V/0.5A, -12V/0.5A, 80W		
TPQ-85CHP	5V/7A, 15V/2.5A, -5V/0.5A, -15V/0.5A, 82W		
TPQ-85DHP	5V/6A, 12V/2A, 24V/1A, -12V/0.5A, 84W	88-132VCA/ 176-264VCD	199X98X38MM
TPQ-125BHP	5V/11A, 12V/4.5A, -5V/1A, -12V/0.5A, 120W		
TPQ-125CHP	5V/10A, 15V/4A, -5V/1A, -15V/0.5A, 122W		
TPQ-125DHP	5V/8A, 12V/2.5A, 24V/2A, -12V/0.5A, 124W		

FUENTES DE VOLTAJE SWITCHEADAS (HP HIGH PERFORMANCE)



FUENTES DE MONTAJE EN RIEL DIN (HP)

MODELO	VOLTAJE SALIDA	V. ENTRADA	DIMENSIONES
TPSR-15-5HP	5V/2.4A/12W	85-264VCA/ 120-370VCD	17.5X90X55MM
TPSR-15-12HP	12V/1.25A/15W		
TPSR-15-24HP	24V/0.63A/15W		
TPSR-15-48HP	48V/0.32A/15W		
TPSR-30-5HP	5V/3A/15W		35X90X54MM
TPSR-30-12HP	12V/2A/24W		
TPSR-30-24HP	24V/1.5A/36W		
TPSR-30-48HP	48V/0.75A/36W		
TPSR-60-5HP	5V/6.5A/32W		52.5X90X54.5MM
TPSR-60-12HP	12V/4.5A/54W		
TPSR-60-24HP	24V/2.5A/60W		
TPSR-60-48HP	48V/1.25A/60W		
TPSR-100-12HP	12V/7.5A/90W		55X90X100MM
TPSR-100-24HP	24V/4A/96W		
TPSR-100-48HP	48V/2A/96W		
TPSR-240-24HP	24V/10A/240W		
TPSR-240-48HP	48V/5A/240W		
TPSR-480-24HP	24V/20A/480W	180-264VCA/ 250-370VCD	227X125.2X100MM
TPSR-480-48HP	48V/10A/480W		
TPSR-960-24HP	24V/40A/960W	180-264VCA/ 254-370VCD	110X125.2X150MM
TPSR-960-48HP	48V/20A/960W		



TPSR-25



TPSR-45



TPSR-72



TPSR-120

FUENTES DE MONTAJE EN RIEL DIN

MODELO	VOLTAJE SALIDA	V. ENTRADA	DIMENSIONES
TPSR-25-12	12V/2.08A/25W	90/264VCA	104X35X45MM
TPSR-50-12	12V/4.02A/50W	100/240VCA	104X76X45MM
TPSR-25-24*	24V/1.04A/25W		104X35X45MM
TPSR-50-24	24V/2.01A/50W		104X76X45MM
TPSR-100-24	24V/4.2A/100W	100-120/ 200-240VCA	10X83X49MM
TPSR-300-24*	24V/12.5A/300W	100/240VCA	100X110X60MM
TPSR-45-12*	12V/3.75A/45W		100X83X49MM
TPSR-72-12	12V/6A/72W		100X60X110MM
TPSR-120-12	12V/10A/120W	90/264VCA	100X110X90MM
TPSR-24-24*	24V/1A/24W		104X76X45MM
TPSR-45-24*	24V/1.87A/45W		100X83X49MM
TPSR-72-24	24V/3A/72W		100X60X110MM
TPSR-120-24	24V/5A/120W	100/240VCA	100X110X90MM



TPSR-15/30/60



TPSR-100



TPSR-240/480



TPSR-960